

BikeAcuteShoulder400uA129'TZpd.protocol
 Number of pairs: 96 Total Time: 2: 8:45
 Description: BikeAcuteShoulder400uA129'TZpd

Pair #	F1(Hz)	F2(Hz)	I(uA)	T(min'sec")	Period(ms)	K0	K1	K2	K3	Polarity	Phase	Description
1	18	62	400	1'	2,500	4	16	80	0	Alternative	0	
2	18	162	400	0'30"	2,500	4	16	80	0	Alternative	0	
3	9	62	400	1'	2,500	4	16	80	0	Alternative	0	
4	18	62	400	1'	2,500	4	16	80	0	Alternative	0	
5	124	62	400	1'	2,500	4	16	80	0	Alternative	0	
6	294	62	400	1'	2,500	4	16	80	0	Alternative	0	
7	321	62	400	0'15"	2,500	4	16	80	0	Alternative	0	
8	40	62	400	2'	2,500	4	16	80	0	Alternative	0	
9	702	62	400	1'	2,500	4	16	80	0	Positive	0	
10	40	396	400	4'	2,500	4	16	80	0	Positive	0	
11	40	562	400	4'	2,500	4	16	80	0	Positive	0	
12	991	200	400	1'	2,500	4	16	80	0	Positive	0	
13	94	200	400	2'	2,500	4	16	80	0	Alternative	0	
14	970	200	400	2'	2,500	4	16	80	0	Alternative	0	
15	40	200	400	2'	2,500	4	16	80	0	Alternative	0	
16	991	90	400	1'	2,500	4	16	80	0	Positive	0	
17	40	45	400	1'	2,500	4	16	80	0	Positive	0	
18	417	81	400	0'30"	2,500	4	16	80	0	Positive	0	legjoint
19	396	81	400	0'30"	2,500	4	16	80	0	Positive	0	
20	9	81	400	1'	2,500	4	16	80	0	Alternative	0	
21	991	81	400	1'	2,500	4	16	80	0	Positive	0	
22	124	81	400	2'	2,500	4	16	80	0	Alternative	0	
23	294	81	400	1'	2,500	4	16	80	0	Alternative	0	
24	284	81	400	0'10"	2,500	4	16	80	0	Alternative	0	
25	139	81	400	1'	2,500	4	16	80	0	Alternative	0	
26	321	81	400	1'	2,500	4	16	80	0	Alternative	0	
27	40	81	400	4'	2,500	4	16	80	0	Alternative	0	
28	9	142	400	1'	2,500	4	16	80	0	Alternative	0	
29	124	142	400	1'	2,500	4	16	80	0	Alternative	0	
30	294	142	400	1'	2,500	4	16	80	0	Alternative	0	
31	284	142	400	0'10"	2,500	4	16	80	0	Alternative	0	
32	321	142	400	1'	2,500	4	16	80	0	Alternative	0	
33	40	142	400	2'	2,500	4	16	80	0	Alternative	0	
34	702	142	400	1'	2,500	4	16	80	0	Positive	0	
35	18	76	400	1'	2,500	4	16	80	0	Alternative	0	
36	9	76	400	0'30"	2,500	4	16	80	0	Alternative	0	
37	124	76	400	1'	2,500	4	16	80	0	Alternative	0	
38	991	76	400	1'	2,500	4	16	80	0	Positive	0	
39	294	76	400	1'	2,500	4	16	80	0	Alternative	0	
40	284	76	400	0'10"	2,500	4	16	80	0	Positive	0	
41	321	76	400	1'	2,500	4	16	80	0	Positive	0	
42	40	76	400	4'	2,500	4	16	80	0	Alternative	0	
43	11	76	400	0'15"	2,500	4	16	80	0	Positive	0	
44	702	76	400	1'	2,500	4	16	80	0	Positive	0	
45	124	480	400	2'	2,500	4	16	80	0	Alternative	0	
46	294	480	400	1'	2,500	4	16	80	0	Alternative	0	
47	284	480	400	0'10"	2,500	4	16	80	0	Alternative	0	
48	321	480	400	1'	2,500	4	16	80	0	Alternative	0	
49	40	480	400	4'	2,500	4	16	80	0	Alternative	0	
50	11	480	400	0'30"	2,500	4	16	80	0	Positive	0	
51	702	480	400	1'	2,500	4	16	80	0	Positive	0	
52	124	195	400	1'	2,500	4	16	80	0	Alternative	0	
53	294	195	400	1'	2,500	4	16	80	0	Alternative	0	
54	284	195	400	0'10"	2,500	4	16	80	0	Alternative	0	
55	321	195	400	1'	2,500	4	16	80	0	Alternative	0	
56	40	195	400	4'	2,500	4	16	80	0	Alternative	0	
57	11	195	400	0'15"	2,500	4	16	80	0	Positive	0	
58	702	195	400	1'	2,500	4	16	80	0	Positive	0	

BikeAcuteShoulder400uA129'TZpd.protocol (Continued 1)

Pair #	F1(Hz)	F2(Hz)	I(uA)	T(min'sec")	Period(ms)	K0	K1	K2	K3	Polarity	Phase	Description
59	124	100	400	4'	2,500	4	16	80	0	Alternative	0	
60	294	100	400	1'	2,500	4	16	80	0	Alternative	0	
61	284	100	400	0'10"	2,500	4	16	80	0	Alternative	0	
62	321	100	400	1'	2,500	4	16	80	0	Alternative	0	
63	40	100	400	4'	2,500	4	16	80	0	Alternative	0	
64	11	100	400	0'15"	2,500	4	16	80	0	Alternative	0	
65	702	100	400	1'	2,500	4	16	80	0	Alternative	0	
66	124	191	400	4'	2,500	4	16	80	0	Alternative	0	
67	294	191	400	1'	2,500	4	16	80	0	Alternative	0	
68	284	191	400	0'10"	2,500	4	16	80	0	Alternative	0	
69	321	191	400	1'	2,500	4	16	80	0	Alternative	0	
70	40	191	400	4'	2,500	4	16	80	0	Alternative	0	
71	11	191	400	0'15"	2,500	4	16	80	0	Positive	0	
72	702	191	400	1'	2,500	4	16	80	0	Positive	0	
73	124	783	400	1'	2,500	4	16	80	0	Alternative	0	
74	294	783	400	1'	2,500	4	16	80	0	Alternative	0	
75	284	783	400	0'10"	2,500	4	16	80	0	Alternative	0	
76	321	783	400	1'	2,500	4	16	80	0	Alternative	0	
77	40	783	400	4'	2,500	4	16	80	0	Alternative	0	
78	11	783	400	0'15"	2,500	4	16	80	0	Positive	0	
79	702	783	400	1'	2,500	4	16	80	0	Positive	0	
80	81	783	400	1'	2,500	4	16	80	0	Alternative	0	
81	124	157	400	2'	2,500	4	16	80	0	Alternative	0	
82	294	157	400	1'	2,500	4	16	80	0	Alternative	0	
83	284	157	400	0'10"	2,500	4	16	80	0	Alternative	0	
84	321	157	400	0'15"	2,500	4	16	80	0	Alternative	0	
85	40	157	400	4'	2,500	4	16	80	0	Alternative	0	
86	11	157	400	0'15"	2,500	4	16	80	0	Positive	0	
87	702	157	400	1'	2,500	4	16	80	0	Positive	0	
88	81	157	400	1'	2,500	4	16	80	0	Alternative	0	
89	11	81	400	1'	2,500	4	16	80	0	Positive	0	
90	702	81	400	4'	2,500	4	16	80	0	Positive	0	
91	40	116	400	2'	2,500	4	16	80	0	Positive	0	
92	40	13	400	1'	2,500	4	16	80	0	Positive	0	
93	14	13	400	2'	2,500	4	16	80	0	Positive	0	
94	50	13	400	2'	2,500	4	16	80	0	Positive	0	
95	35	102	400	0'30"	2,500	4	16	80	0	Alternative	0	
96	81	84	400	0'15"	2,500	4	16	80	0	Alternative	0	