

BikeAcuteFracture380uA101'pd.protocol  
 Number of pairs: 54 Total Time: 1:41:45  
 Description: BikeAcuteFracture380uA102'TZpd

Pair #	F1(Hz)	F2(Hz)	I(uA)	T(min'sec")	Period(ms)	K0	K1	K2	K3	Polarity	Phase	Description
1	18	62	380	1'	2,500	4	16	80	0	Alternative	0	
2	18	59	380	2'	2,500	4	16	80	0	Alternative	0	
3	18	39	380	2'	2,500	4	16	80	0	Alternative	0	
4	18	238	380	2'	2,500	4	16	80	0	Alternative	0	
5	18	162	380	0'30"	2,500	4	16	80	0	Alternative	0	
6	417	59	380	0'15"	2,500	4	16	80	0	Positive	0	legjoint
7	417	39	380	0'15"	2,500	4	16	80	0	Positive	0	
8	396	59	380	0'15"	2,500	4	16	80	0	Positive	0	
9	396	39	380	0'15"	2,500	4	16	80	0	Positive	0	
10	124	59	380	5'	2,500	4	16	80	0	Alternative	0	
11	124	39	380	5'	2,500	4	16	80	0	Alternative	0	
12	124	783	380	5'	2,500	4	16	80	0	Alternative	0	
13	991	59	380	1'	2,500	4	16	80	0	Positive	0	
14	991	39	380	1'	2,500	4	16	80	0	Positive	0	
15	991	783	380	1'	2,500	4	16	80	0	Positive	0	
16	294	59	380	1'	2,500	4	16	80	0	Alternative	0	
17	294	39	380	1'	2,500	4	16	80	0	Alternative	0	
18	294	783	380	1'	2,500	4	16	80	0	Alternative	0	
19	40	59	380	4'	2,500	4	16	80	0	Alternative	0	
20	40	39	380	4'	2,500	4	16	80	0	Alternative	0	
21	40	783	380	4'	2,500	4	16	80	0	Alternative	0	
22	40	238	380	4'	2,500	4	16	80	0	Alternative	0	
23	40	100	380	4'	2,500	4	16	80	0	Alternative	0	
24	40	191	380	4'	2,500	4	16	80	0	Alternative	0	
25	40	62	380	4'	2,500	4	16	80	0	Alternative	0	
26	40	116	380	2'	2,500	4	16	80	0	Alternative	0	
27	124	59	380	2'	2,500	4	16	80	0	Alternative	0	
28	124	39	380	2'	2,500	4	16	80	0	Alternative	0	
29	124	783	380	2'	2,500	4	16	80	0	Alternative	0	
30	124	100	380	1'	2,500	4	16	80	0	Alternative	0	
31	124	191	380	1'	2,500	4	16	80	0	Alternative	0	
32	284	59	380	1'	2,500	4	16	80	0	Alternative	0	
33	284	39	380	1'	2,500	4	16	80	0	Alternative	0	
34	284	783	380	1'	2,500	4	16	80	0	Alternative	0	
35	284	62	380	1'	2,500	4	16	80	0	Alternative	0	
36	284	142	380	1'	2,500	4	16	80	0	Alternative	0	
37	284	238	380	1'	2,500	4	16	80	0	Alternative	0	
38	40	396	380	4'	2,500	4	16	80	0	Positive	0	
39	40	562	380	4'	2,500	4	16	80	0	Positive	0	
40	991	200	380	1'	2,500	4	16	80	0	Positive	0	
41	94	200	380	2'	2,500	4	16	80	0	Alternative	0	
42	970	200	380	2'	2,500	4	16	80	0	Alternative	0	
43	40	200	380	2'	2,500	4	16	80	0	Alternative	0	
44	40	45	380	1'	2,500	4	16	80	0	Positive	0	
45	991	90	380	1'	2,500	4	16	80	0	Positive	0	
46	81	90	380	1'	2,500	4	16	80	0	Positive	0	
47	702	59	380	2'	2,500	4	16	80	0	Positive	0	
48	702	39	380	2'	2,500	4	16	80	0	Positive	0	
49	702	783	380	2'	2,500	4	16	80	0	Positive	0	
50	81	142	380	1'	2,500	4	16	80	0	Alternative	0	
51	81	783	380	1'	2,500	4	16	80	0	Alternative	0	
52	81	59	380	1'	2,500	4	16	80	0	Alternative	0	
53	81	39	380	1'	2,500	4	16	80	0	Alternative	0	
54	35	102	380	0'15"	2,500	4	16	80	0	Alternative	0	