

BikeAcuteLeg400uA130'TZpd.protocol
 Number of pairs: 92 Total Time: 2:10: 0
 Description: BikeAcuteLeg400uA130'TZpd

Pair #	F1(Hz)	F2(Hz)	I(uA)	T(min'sec")	Period(ms)	K0	K1	K2	K3	Polarity	Phase	Description
1	18	62	400	1'	2,500	4	16	80	0	Alternative	0	
2	18	162	400	0'30"	2,500	4	16	80	0	Alternative	0	
3	9	62	400	1'	2,500	4	16	80	0	Alternative	0	
4	991	62	400	1'	2,500	4	16	80	0	Positive	0	
5	124	62	400	1'	2,500	4	16	80	0	Alternative	0	
6	294	62	400	1'	2,500	4	16	80	0	Alternative	0	
7	321	62	400	0'15"	2,500	4	16	80	0	Alternative	0	
8	40	62	400	4'	2,500	4	16	80	0	Alternative	0	
9	702	62	400	1'	2,500	4	16	80	0	Positive	0	
10	40	396	400	4'	2,500	4	16	80	0	Positive	0	
11	40	562	400	4'	2,500	4	16	80	0	Positive	0	
12	991	200	400	1'	2,500	4	16	80	0	Positive	0	
13	94	200	400	2'	2,500	4	16	80	0	Alternative	0	
14	970	200	400	2'	2,500	4	16	80	0	Alternative	0	
15	40	200	400	2'	2,500	4	16	80	0	Alternative	0	
16	991	1	400	1'	2,500	4	16	80	0	Positive	0	
17	991	45	400	2'	2,500	4	16	80	0	Positive	0	
18	40	45	400	1'	2,500	4	16	80	0	Positive	0	
19	417	18	400	0'30"	2,500	4	16	80	0	Positive	0	legjoint
20	396	18	400	0'30"	2,500	4	16	80	0	Positive	0	
21	991	18	400	1'	2,500	4	16	80	0	Positive	0	
22	9	18	400	1'	2,500	4	16	80	0	Alternative	0	
23	124	18	400	2'	2,500	4	16	80	0	Alternative	0	
24	294	18	400	1'	2,500	4	16	80	0	Alternative	0	
25	284	18	400	0'10"	2,500	4	16	80	0	Alternative	0	
26	139	18	400	1'	2,500	4	16	80	0	Alternative	0	
27	321	18	400	0'15"	2,500	4	16	80	0	Alternative	0	
28	40	18	400	4'	2,500	4	16	80	0	Alternative	0	
29	9	142	400	1'	2,500	4	16	80	0	Alternative	0	
30	124	142	400	1'	2,500	4	16	80	0	Alternative	0	
31	294	142	400	1'	2,500	4	16	80	0	Alternative	0	
32	284	142	400	0'10"	2,500	4	16	80	0	Alternative	0	
33	321	142	400	0'15"	2,500	4	16	80	0	Alternative	0	
34	40	142	400	2'	2,500	4	16	80	0	Alternative	0	
35	702	142	400	1'	2,500	4	16	80	0	Positive	0	
36	9	77	400	1'	2,500	4	16	80	0	Alternative	0	
37	124	77	400	1'	2,500	4	16	80	0	Alternative	0	
38	294	77	400	1'	2,500	4	16	80	0	Alternative	0	
39	284	77	400	0'10"	2,500	4	16	80	0	Positive	0	
40	321	77	400	1'	2,500	4	16	80	0	Positive	0	
41	40	77	400	4'	2,500	4	16	80	0	Alternative	0	
42	11	77	400	0'15"	2,500	4	16	80	0	Positive	0	
43	702	77	400	4'	2,500	4	16	80	0	Positive	0	
44	124	480	400	2'	2,500	4	16	80	0	Alternative	0	
45	294	480	400	1'	2,500	4	16	80	0	Alternative	0	
46	284	480	400	0'10"	2,500	4	16	80	0	Alternative	0	
47	321	480	400	0'15"	2,500	4	16	80	0	Alternative	0	
48	40	480	400	4'	2,500	4	16	80	0	Alternative	0	
49	11	480	400	0'30"	2,500	4	16	80	0	Positive	0	
50	702	480	400	1'	2,500	4	16	80	0	Positive	0	
51	124	195	400	1'	2,500	4	16	80	0	Alternative	0	
52	294	195	400	1'	2,500	4	16	80	0	Alternative	0	
53	284	195	400	0'10"	2,500	4	16	80	0	Alternative	0	
54	321	195	400	0'15"	2,500	4	16	80	0	Alternative	0	
55	40	195	400	4'	2,500	4	16	80	0	Alternative	0	
56	124	100	400	4'	2,500	4	16	80	0	Alternative	0	
57	294	100	400	1'	2,500	4	16	80	0	Alternative	0	
58	284	100	400	0'10"	2,500	4	16	80	0	Alternative	0	

BikeAcuteLeg400uA130'TZpd.protocol (Continued 1)

Pair #	F1(Hz)	F2(Hz)	I(uA)	T(min'sec")	Period(ms)	K0	K1	K2	K3	Polarity	Phase	Description
59	321	100	400	0'15"	2,500	4	16	80	0	Alternative	0	
60	40	100	400	4'	2,500	4	16	80	0	Alternative	0	
61	11	100	400	0'15"	2,500	4	16	80	0	Positive	0	
62	702	100	400	2'	2,500	4	16	80	0	Positive	0	
63	124	191	400	4'	2,500	4	16	80	0	Alternative	0	
64	991	100	400	1'	2,500	4	16	80	0	Positive	0	
65	294	191	400	1'	2,500	4	16	80	0	Alternative	0	
66	284	191	400	0'10"	2,500	4	16	80	0	Alternative	0	
67	321	191	400	0'15"	2,500	4	16	80	0	Alternative	0	
68	40	191	400	4'	2,500	4	16	80	0	Alternative	0	
69	11	191	400	0'30"	2,500	4	16	80	0	Positive	0	
70	702	191	400	1'	2,500	4	16	80	0	Positive	0	
71	124	783	400	1'	2,500	4	16	80	0	Alternative	0	
72	294	783	400	1'	2,500	4	16	80	0	Alternative	0	
73	284	783	400	0'10"	2,500	4	16	80	0	Alternative	0	
74	321	783	400	0'15"	2,500	4	16	80	0	Alternative	0	
75	11	783	400	0'30"	2,500	4	16	80	0	Positive	0	
76	40	783	400	4'	2,500	4	16	80	0	Alternative	0	
77	702	783	400	1'	2,500	4	16	80	0	Positive	0	
78	81	783	400	1'	2,500	4	16	80	0	Alternative	0	
79	124	157	400	2'	2,500	4	16	80	0	Alternative	0	
80	294	157	400	1'	2,500	4	16	80	0	Alternative	0	
81	284	157	400	0'10"	2,500	4	16	80	0	Alternative	0	
82	321	157	400	0'15"	2,500	4	16	80	0	Alternative	0	
83	40	157	400	4'	2,500	4	16	80	0	Alternative	0	
84	81	157	400	1'	2,500	4	16	80	0	Alternative	0	
85	11	18	400	1'	2,500	4	16	80	0	Positive	0	
86	702	18	400	4'	2,500	4	16	80	0	Positive	0	
87	40	116	400	2'	2,500	4	16	80	0	Positive	0	
88	40	13	400	2'	2,500	4	16	80	0	Positive	0	
89	14	13	400	2'	2,500	4	16	80	0	Positive	0	
90	50	13	400	2'	2,500	4	16	80	0	Positive	0	
91	35	102	400	0'30"	2,500	4	16	80	0	Alternative	0	
92	81	84	400	0'15"	2,500	4	16	80	0	Alternative	0	